

## 1z0-001 braindumps

### Oracle 9i Internet Application Developer

**1z0-001: 9i Internet Application Developer Introduction to Oracle: SQL and PL/SQL**

**Practice Exam:** 1z0-001 Exams

**Exam Number/Code:** 1z0-001

**Exam Name:** 9i Internet Application Developer Introduction to Oracle: SQL and PL/SQL

**Questions and Answers:** 171 Q&As

( [9i Internet Application Developer](#) )



Exam : [1z0-001](#)

"9i Internet Application Developer Introduction to Oracle: SQL and PL/SQL", also known as 1z0-001 exam, is a Oracle certification. With the complete collection of exam questions, Just4Study has assembled to take you through 171 Q&As to your 1z0-001 exam preparation. In the 1z0-001 exam resources, you will cover every field and category in Oracle Certification helping to ready you for your successful Oracle Certification.

The exam questions cover the latest real test and with all the correct answer. we promise the Q&A for Oracle 9i Internet Application Developer 1z0-001 (9i Internet Application Developer Introduction to Oracle: SQL and PL/SQL) examination of original title complete coverage. 1z0-001 exam questions help you pass the exam.

#### **Just4Study 1z0-001 Feature:**

\* High quality - High quality and valued for the 1z0-001 Exam: 100% Guarantee to Pass Your 1z0-001 exam and get your 9i Internet Application Developer certification.

\* Authoritative - Authoritative braindumps with complete details about 1z0-001 exam.

\* Cheaper - Our Just4Study products are cheaper than any other website. With our completed 9i Internet Application Developer resources, you will minimize your **Oracle 9i Internet Application Developer** cost and be ready to pass your 1z0-001 exam on Your First Try, 100% Money Back Guarantee included!

\* Free - Try free 9i Internet Application Developer demo before you decide to buy it in <http://www.Just4Study.com>.

#### **Just4Study Guarantee:**

Just4Study provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if you do not pass the 1z0-001 exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

#### **Free 1z0-001 Demo Download**

Just4Study offers free demo for 9i Internet Application Developer 1z0-001 exam (9i Internet Application Developer Introduction to Oracle: SQL and PL/SQL). You can check out the interface, question quality and usability of our practice exams before you decide to buy it. We are the only one site can offer demo for almost all products.

The Questions & Answers cover the latest real test and with all the correct answer.we promise the Q&A for **Oracle 9i Internet Application Developer 1z0-001** examination of original title complete coverage.1z0-001 Questions & Answers help you pass the exam. Otherwise,we will give you a full refund.

**VUE/Prometric Code: 1z0-001**

Exam Name: 9i Internet Application Developer Introduction to Oracle: SQL and PL/SQL( 9i Internet Application Developer )

**Oracle 1z0-001** Test belongs to one of the 9i Internet Application Developer certified test, if needs to obtain the 9i Internet Application Developer certificate, you also need to participate in other related test, the details you may visit the [9i Internet Application Developer](#) certified topic, in there, you will see all related 9i Internet Application Developer certified subject of examination.

Just4Study professional provide 9i Internet Application Developer 1z0-001 the newest Q&A, completely covers 1z0-001 test original topic. With our complete 9i Internet Application Developer resources, you will minimize your 9i Internet Application Developer cost and be ready to pass your 1z0-001 tests on Your First Try, 100% Money Back Guarantee included!

### **Just4Study Help You Pass Any IT Exam**

**Just4Study.com** offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.

Exam : Oracle 1Z0-001

Title : INTRODUCTION TO ORACLE: SQL AND PL/SQL

1. Your company wants to give each employee a \$100 salary increment. You need to evaluate the results from the EMP table prior to the actual modification. If you do not want to store the results in the database, which statement is valid?

- A. You need to add a column to the EMP table.
- B. You need to give the arithmetic expression that involves the salary increment in the SET clause of the UPDATE statement.
- C. You need to give the arithmetic expression that involves the salary increment in the SELECT clause of the SELECT statement.
- D. You need to give the arithmetic expression that involves the salary increment in the UPDATE clause of the SELECT statement.
- E. You need to give the arithmetic expression that involves the salary increment in the DISPLAY clause of the SELECT statement.

Answer: C

2. Examine the declaration section:

```
DECLARE
CURSOR emp_cursor(p_deptno NUMBER, p_job VARCHAR2)
IS
SELECT empno, ename
FROM emp
WHERE deptno = p_deptno
AND job = p_job;
BEGIN
...
```

Which statement opens this cursor successfully?

- A. OPEN emp\_cursor;
- B. OPEN emp\_cursor('Clerk', 10);
- C. OPEN emp\_cursor(10,'Analyst');
- D. OPEN emp\_cursor(p\_deptno, p\_job);

Answer: C

3. Click on the EXHIBIT button and examine the table instance chart for the cars table.

Which SELECT statement will display style, color, and lot number for all cars based on the model entered at the prompt, regardless of case?

- A. SELECT style, color, lot\_no  
FROM cars  
WHERE model = UPPER('&model');
- B. SELECT style, color, lot\_no  
FROM cars  
WHERE model = '&model';
- C. SELECT style, color, lot\_no  
FROM cars  
WHERE UPPER(model) = UPPER('&model');
- D. SELECT style, color, lot\_no  
FROM cars  
WHERE UPPER(model) = '&model';

Answer: C

4. Which ALTER command would you use to reinstate a disabled primary key constraint?

- A. ALTER TABLE cars  
ENABLE PRIMARY KEY (id);
- B. ALTER TABLE cars  
ENABLE CONSTRAINT cars\_id\_pk;
- C. ALTER TABLE cars  
ENABLE PRIMARY KEY (id) CASCADE;
- D. ALTER TABLE cars  
ADD CONSTRAINT cars\_id\_pk PRIMARY KEY (id);

Answer: B

5. The PRODUCT table contains these columns:

ID NUMBER(9) PK  
COST NUMBER(7,2)  
SALE\_PRICE NUMBER(7,2)

Management has asked you to calculate the net revenue per unit for each product if the cost of each product is increased by 10% and the sale price of each product is increased by 25%.

You issue this SQL statement:

```
SELECT id, sale_price * 1.25 - cost * 1.10  
FROM product;
```

Which conclusion can you draw from the results?

- A. Only the required results are displayed.
- B. The results provide more information than management requested.
- C. A function needs to be included in the SELECT statement to achieve the desired results.
- D. The order of the operations in the calculation needs to be changed to achieve the required results.

Answer: A

6. Click on the EXHIBIT button and examine the structure of the DEPARTMENT and EMPLOYEE tables.

Evaluate this SQL statement:

```
CREATE INDEX emp_dept_id_idx  
ON employee(dept_id);
```

Which result will the statement provide?

- A. Store an index in the EMPLOYEE table.
- B. Increase the chance of full table scans.
- C. May reduce the amount of disk I/O for SELECT statements.
- D. May reduce the amount of disk I/O for INSERT statements.
- E. Override the unique index created when the FK relationship was defined.

Answer: C

7. You want to display the average salary for departments 20 and 50, but only if those departments have an average salary of at least 2000. Which statement will produce the required results?

- A. SELECT deptno, AVG(sal)  
FROM emp  
WHERE deptno IN (20, 50)  
GROUP BY deptno  
HAVING AVG(sal) >= 2000;
- B. SELECT deptno, AVG(sal)  
FROM emp  
GROUP BY deptno  
HAVING AVG(sal) >= 2000  
AND deptno IN (20, 50);
- C. SELECT deptno, AVG(sal)  
FROM emp  
WHERE deptno IN (20, 50)  
AND AVG(sal) >= 2000  
GROUP BY deptno;
- D. SELECT deptno, AVG(sal)  
FROM emp  
WHERE deptno IN (20, 50)  
GROUP BY AVG(sal)  
HAVING AVG(sal) >= 2000;

Answer: A

8. Click on the EXHIBIT button and examine the table instance chart for the cars table.

You query the database with this command:

```
SELECT lot_no "Lot Number", COUNT(*) "Number of Cars Available"  
FROM cars  
WHERE model = 'Fire'  
GROUP BY lot_no  
HAVING COUNT(*) > 10  
ORDER BY COUNT(*);
```

Which clause restricts which groups are displayed?

- A. SELECT lot\_no "Lot Number", COUNT(\*) "Number of Cars Available"
- B. WHERE model = 'Fire'
- C. HAVING COUNT(\*) > 10
- D. GROUP BY lot\_no
- E. ORDER BY COUNT(\*)

Answer: C

9. The structure of the DEPT table is as follows:

Name Null? Type

```
-----  
DEPTNO NOT NULL NUMBER(2)  
DNAME VARCHAR2(14)  
LOC VARCHAR2(13)
```

Examine the code:

```
DECLARE  
TYPE dept_record_type IS RECORD  
(dno NUMBER,  
name VARCHAR2(20));
```

```
dept_rec dept_record_type;
BEGIN
SELECT deptno, dname
INTO dept_rec
FROM dept
WHERE deptno = 10;
END;
```

Which statement displays the name of the selected department?

- A. DBMS\_OUTPUT.PUT\_LINE(name);
- B. DBMS\_OUTPUT.PUT\_LINE(dname);
- C. DBMS\_OUTPUT.PUT\_LINE(dept\_rec.name);
- D. DBMS\_OUTPUT.PUT\_LINE(dept\_rec.dname);
- E. DBMS\_OUTPUT.PUT\_LINE(dept\_rec(name));

Answer: C

10. Which should you do after each FETCH statement in a PL/SQL block?

- A. Open the cursor.
- B. Close the cursor.
- C. Initialize the loop.
- D. Test for rows using a cursor attribute.

Answer: D

11. Which statement is valid within the executable section of a PL/SQL block?

- A. BEGIN  
emp\_rec emp%ROWTYPE;  
END;
- B. WHEN NO\_DATA\_FOUND THEN  
DBMS\_OUTPUT.PUT\_LINE ('No records found');
- C. SELECT ename, sal  
INTO v\_ename, v\_sal  
FROM emp  
WHERE empno = 101;
- D. PROCEDURE calc\_max (n1 NUMBER,n2 NUMBER,p\_max OUT NUMBER) IS  
BEGIN  
IF n1 > n2 THEN  
p\_max := n1;  
ELSE  
p\_max := n2;  
END;

Answer: C

12. Click on the EXHIBIT button and examine the table instance chart for the patient table.

You need to create the patient\_id\_seq sequence to be used with the patient table's primary key column. The sequence should begin at 1000, have a maximum value of 999999999, never reuse any numbers, and increment by 1.

Which statement would you use to complete this task?

- A. CREATE SEQUENCE patient\_id\_seq  
START WITH 1000  
MAXVALUE 999999999  
NOCYCLE;
- B. CREATE SEQUENCE patient\_id\_seq  
START WITH 1000  
MAXVALUE 999999999  
STEP BY 1;

```
C. CREATE SEQUENCE patient_id_seq
ON patient (patient_id)
MINVALUE 1000
MAXVALUE 999999999
INCREMENT BY 1
NOCYCLE;
```

D. This task cannot be accomplished.

Answer: A

13. Evaluate this IF statement:

```
IF v_value > 100 THEN
v_new_value := 2 * v_value;
ELSIF v_value > 200 THEN
v_new_value := 3 * v_value;
ELSIF v_value < 300 THEN
v_new_value := 4 * v_value;
ELSE
v_new_value := 5 * v_value;
END IF;
```

What would be assigned to V\_NEW\_VALUE if V\_VALUE is 250?

- A. 250
- B. 500
- C. 750
- D. 1000
- E. 1250

Answer: B

14. Given this executable section of a PL/SQL block:

```
BEGIN
FOR employee_record IN salary_cursor LOOP
employee_id_table(employee_id) :=
employee_record.last_name;
END LOOP;
CLOSE salary_cursor;
END;
```

Why does this section cause an error?

- A. The cursor needs to be opened.
- B. No FETCH statements were issued.
- C. Terminating conditions are missing.
- D. The cursor does not need to be closed.

Answer: D

15. You need to execute a script file named QUERYEMP.SQL from your SQL\*Plus environment. Which command do you use?

- A. RUN QUERYEMP
- B. GET QUERYEMP
- C. START QUERYEMP
- D. EXECUTE QUERYEMP

Answer: C

16. The EMPLOYEE table contains these columns:

```
BONUSNUMBER(7,2)
DEPT_ID NUMBER(9)
```

There are 10 departments and each department has at least 1 employee. Bonus values are greater than 500; not all employees receive a bonus.

Evaluate this PL/SQL block:

```
DECLARE
v_bonusemployee.bonus%TYPE := 300;
BEGIN
UPDATE employee
SET bonus = bonus + v_bonus
WHERE dept_id IN (10, 20, 30);
COMMIT;
END;
```

What will be the result?

- A. All employees will be given a 300 bonus.
- B. A subset of employees will be given a 300 bonus.
- C. All employees will be given a 300 increase in bonus.
- D. A subset of employees will be given a 300 increase in bonus.

Answer: D

17. Examine this block of code:

```
SET SERVEROUTPUT ON
DECLARE
x NUMBER;
v_sal NUMBER;
v_found VARCHAR2(10) := 'TRUE';
BEGIN
x := 1;
v_sal := 1000;
DECLARE
v_found VARCHAR2(10);
y NUMBER;
BEGIN
IF (v_sal > 500) THEN
v_found := 'YES';
END IF;
DBMS_OUTPUT.PUT_LINE ('Value of v_found is '|| v_found);
DBMS_OUTPUT.PUT_LINE ('Value of v_sal is '|| v_sal);
y := 20;
END;
DBMS_OUTPUT.PUT_LINE ('Value of v_found is '|| v_found);
DBMS_OUTPUT.PUT_LINE ('Value of Y is '|| TO_CHAR(y));
END;
SET SERVEROUTPUT OFF
```

What is the result of executing this block of code?

- A. PLS-00201: identifier 'Y' must be declared
- B. Value of v\_found is YES  
Value of v\_sal is 1000  
Value of v\_found is TRUE
- C. Value of v\_found is YES  
Value of v\_sal is 1000  
Value of v\_found is YES  
Value of Y is 20
- D. PLS-00201: identifier 'v\_sal' must be declared  
PLS-00201: identifier 'Y' must be declared

E. Value of v\_found is YES

Value of v\_sal is 1000

Value of v\_found is TRUE

Value of Y is 20

Answer: A

18. Examine this block of code:

```
SET SERVEROUTPUT ON
DECLARE
x NUMBER;
v_sal NUMBER;
v_found VARCHAR2(10) := 'TRUE';
BEGIN
x := 1;
v_sal := 1000;
DECLARE
v_found VARCHAR2(10);
y NUMBER;
BEGIN
IF (v_sal > 500) THEN
v_found := 'YES';
END IF;
DBMS_OUTPUT.PUT_LINE ('Value of v_found is '|| v_found);
DBMS_OUTPUT.PUT_LINE ('Value of v_sal is '|| v_sal);
y := 20;
END;
DBMS_OUTPUT.PUT_LINE ('Value of v_found is '|| v_found);
DBMS_OUTPUT.PUT_LINE ('Value of Y is '|| TO_CHAR(y));
END;
SET SERVEROUTPUT OFF
```

Why does this code produce an error when executed?

- A. The value of V\_FOUND cannot be 'YES'.
- B. Variable V\_FOUND is declared at more than one location.
- C. Variable Y is declared in the inner block and referenced in the outer block.
- D. Variable V\_SAL is declared in the outer block and referenced in the inner block.

Answer: C

19. You need to perform a major update on the EMPLOYEE table. You have decided to disable the PRIMARY KEY constraint on the empid column and the CHECK constraint on the job column.

What happens when you try to enable the constraints after the update is completed?

- A. You need to recreate the constraints once they are disabled.
- B. Any existing rows that do not confirm with the constraints are automatically deleted.
- C. Only the future values are verified to confirm with the constraints, leaving the existing values unchecked.
- D. The indexes on both the columns with the PRIMARY KEY constraint and the CHECK constraint are automatically re-created.
- E. All the existing column values are verified to confirm with the constraints and an error message is generated if any existing values do not confirm.

Answer: E

20. You issue this command:

```
CREATE SYNONYM emp
FOR ed.employee;
```

Which task has been accomplished?

- A. The need to qualify an object name with its schema was eliminated for user Ed.
- B. The need to qualify an object name with its schema was eliminated for only you.
- C. The need to qualify an object name with its schema was eliminated for all users.
- D. The need to qualify an object name with its schema was eliminated for users with access.

Answer: B

**[1z0-001 Braindumps](#)**

**Related 1z0-001 Exams**

[1z0-147](#) oracle9i program with pl/sql

[1z0-101](#) develop pl/sql program units

[1z0-001](#) 9i Internet Application Developer Introduction to Oracle: SQL and PL/SQL

[1z0-141](#) oracle9i forma developer:build internet applications

[1z0-132](#) 9i Internet Application Developer Oracle9i, Build Internet Applications II

[1z0-140](#) oracle9i forms developer:new features

[1z0-131](#) 9i Internet Application Developer Oracle9i, Build Internet Applications I

**Other Oracle Exams**

[1z0-221](#)    [1Z0-041](#)    [1z0-140](#)    [1z0-030](#)    [1z0-312](#)    [1z0-262](#)    [1z0-271](#)    [1Z1-241](#)

[1z0-010](#)    [1z0-131](#)    [1z0-264](#)    [1z0-222](#)    [1z0-054](#)    [1z1-051](#)    [1z0-241](#)    [1z0-046](#)

[1Z0-200](#)    [1Z0-242](#)    [1Z0-108](#)    [1z0-048](#)