

## 310-220 braindumps

### SUN SCDJWS

**310-220: Sun Certified Developer for Java Web Services**

**Practice Exam:** 310-220 Exams

**Exam Number/Code:** 310-220

**Exam Name:** Sun Certified Developer for Java Web Services

**Questions and Answers:** 250 Q&As

( [SCDJWS](#) )



Exam : [310-220](#)

"Sun Certified Developer for Java Web Services", also known as 310-220 exam, is a SUN certification. With the complete collection of exam questions, Just4Study has assembled to take you through 250 Q&As to your 310-220 exam preparation. In the 310-220 exam resources, you will cover every field and category in SUN Certification helping to ready you for your successful SUN Certification.

The exam questions cover the latest real test and with all the correct answer. we promise the Q&A for SUN SCDJWS 310-220 (Sun Certified Developer for Java Web Services) examination of original title complete coverage. 310-220 exam questions help you pass the exam.

#### **Just4Study 310-220 Feature:**

\* High quality - High quality and valued for the 310-220 Exam: 100% Guarantee to Pass Your 310-220 exam and get your SCDJWS certification.

\* Authoritative - Authoritative braindumps with complete details about 310-220 exam.

\* Cheaper - Our Just4Study products are cheaper than any other website. With our completed SCDJWS resources, you will minimize your **SUN SCDJWS** cost and be ready to pass your 310-220 exam on Your First Try, 100% Money Back Guarantee included!

\* Free - Try free SCDJWS demo before you decide to buy it in <http://www.Just4Study.com>.

#### **Just4Study Guarantee:**

Just4Study provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if you do not pass the 310-220 exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

#### **Free 310-220 Demo Download**

Just4Study offers free demo for SCDJWS 310-220 exam (Sun Certified Developer for Java Web Services). You can check out the interface, question quality and usability of our practice exams before you decide to buy it. We are the only one site can offer demo for almost all products.

The Questions & Answers cover the latest real test and with all the correct answer. we promise the Q&A for **SUN SCDJWS 310-220** examination of original title complete coverage. 310-220 Questions & Answers help you pass the exam. Otherwise, we will give you a full refund.

**VUE/Prometric Code: 310-220**

Exam Name: Sun Certified Developer for Java Web Services( SCDJWS )

Questions and Answers: 250 Q&A

[SUN 310-220](#) Test belongs to one of the SCDJWS certified test, if needs to obtain the SCDJWS certificate, you also need to participate in other related test, the details you may visit the [SCDJWS](#) certified topic, in there, you will see all related SCDJWS certified subject of examination.

Just4Study professional provide SCDJWS 310-220 the newest Q&A, completely covers 310-220 test original topic. With our complete SCDJWS resources, you will minimize your SCDJWS cost and be ready to pass your 310-220 tests on Your First Try, 100% Money Back Guarantee included!

### **Just4Study Help You Pass Any IT Exam**

[Just4Study.com](#) offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.

Exam : SUN 310-220

Title : Sun Certified Developer for Java Web Services

1. Given:

```
<xsd:schema targetNamespace="http://sun.cert/types"
xmlns:suncert="http://sun.cert/types">
<xsd:element name="fooElement" type="suncert:Foo"/>
<xsd:complexType name="Foo">
<xsd:sequence>
<xsd:element name="age" type="xsd:long"/>
<xsd:element name="last" type="xsd:string"/>
<xsd:element name="first" type="xsd:string"
nillable="true"/>
</xsd:sequence>
</xsd:complexType>
</xsd:schema>
```

Which two instances of a fooElement are valid? (Choose two.)

A. <fooElement>

```
<last>Duke</last>
<first xsi:nil="1"/>
</fooElement>
```

B. <fooElement>

```
<age>33</age>
<last>Duke</last>
<first>Monty</first>
</fooElement>
```

C. <fooElement>

```
<age>33</age>
<last>Duke</last>
<first xsi:nil="1"/>
</fooElement>
```

D. <fooElement>

```
<age>33</age>
<last xsi:nil="1"/>
<first>Monty</first>
</fooElement>
```

E. <fooElement>

```
<age>33</age>
<last>Duke</last>
```

```
<first xsi:nil="1">Monty</first>
</fooElement>
```

Answer: BC

2. A developer uses the delete\_tModel function to delete five tModels. Which two describe the behavior of the system after the delete\_tModel is executed? (Choose two.)

- A. The delete\_tModel logically deletes the tModels .
- B. The tModels cannot be accessed since they are permanently deleted.
- C. The deleted tModels still appear in the results returned by find\_tModel.
- D. The deleted tModels are omitted from any results returned by find\_tModel.

Answer: AD

3. A stateful Web service is implemented as an EJB based endpoint. What are two ways to maintain that state? (Choose two.)

- A. by using URL re-writing
- B. by adding a session cookie to the HTTP headers
- C. by adding a conversation id to the SOAP headers
- D. by requiring clients to send a client id parameter to all methods

Answer: CD

4. Which Java type can be used to represent arbitrary XML data in a JAX-RPC service endpoint interface?

- A. org.w3c.dom.Document
- B. javax.xml.soap.SOAPPart
- C. javax.xml.soap.SOAPElement
- D. javax.xml.soap.SOAPException

Answer: C

5. Given:

```
<Schema targetNamespace="http://sun.cert/types"
xmlns:ns0="http://www.w3.org/2001/XMLSchema"
xmlns="http://www.w3.org/2001/XMLSchema"
xmlns:xsd="http://sun.cert/xsdTypes"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<complexType name="Foo">
<sequence>
<!-- insert code here -->
</sequence>
</complexType>
</schema>
```

Assuming that no other namespace declarations exist, which two elements use the long type that is defined in the http://www.w3.org/2001/XMLSchema namespace? (Choose two.)

- A. <element name="length" type="long"/>
- B. <element name="length type="xsi:long"/>
- C. <element name="length" type="xsd:long"/>
- D. <element name="length" type="ns0:long"/>

Answer: AD

6. Given:

- 11: public BulkResponse findCallerAssociations(
- 12: Collection findQualifiers,
- 13: Boolean confirmedByCaller,
- 14: Boolean confirmedByOtherParty,
- 15: Collection associationTypes);

...

```
36: BusinessQueryManager queryMngr =  
37: registry.getBusinessQueryManager();  
38: BulkResponse response =  
39: queryMngr.findCallerAssociations(null,  
40: Boolean.TRUE, Boolean.FALSE, null);
```

A developer has established a JAXR connection to a UDDI registry. The developer executes the findCallerAssociations method that is defined in lines 11-15. The context for the method invocation is shown in lines 36-40. The invocation on line 39-40 will return a BulkResponse object.

Which is true about the BulkResponse object?

- A. It contains a Collection of Association objects that the other party has confirmed with the caller.
- B. It contains a Collection of Organization objects that have confirmed the associations with the caller.
- C. It contains a Collection of Association objects that the other party has NOT yet confirmed with the caller.
- D. It contains a Collection of Key objects representing UUID keys for organizations that have confirmed the associations with the caller.

Answer: C

7. Given:

```
<schema targetNamespace="http://sun.cert/types"  
xmlns:xsd="http://www.w3.org/2001/XMLSchema"  
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"  
xmlns:wSDL="http://schemas.xmlsoap.org/wSDL">  
<!-- insert code here -->  
</schema>
```

Assume all XML fragments are well-formed.

According to the WS-I Basic Profile 1.0a, which type definition can be used to define an array of longs?

A. `<xsd:complexType name="longArray">`

```
<xsd:array>  
<xsd:element name="item" type="xsd:long"/>  
</xsd:array>  
</xsd:complexType>
```

B. `<xsd:complexType name="longArray">`

```
<xsd:sequence>  
<element name="item" type="xsd:long"/>  
</xsd:sequence>  
</xsd:complexType>
```

C. `<xsd:complexType name="longArray">`

```
<xsd:array>  
<xsd:element name="item" type="xsd:long" minOccurs="0"  
maxOccurs="unbounded"/>  
</xsd:array>  
</xsd:complexType>
```

D. `<xsd:complexType name="longArray">`

```
<xsd:sequence>  
<xsd:element name="item" minOccurs="0" maxOccurs="5"  
type="xsd:long"/>  
</xsd:sequence>  
</xsd:complexType>
```

Answer: D

8. A developer in a business-to-business environment is required to build a Web service client that can be strongly authenticated by a Web service.

What must the developer do to create the client?

- A. use role-based security
- B. implement form-based security
- C. implement basic authentication
- D. provide a digital certificate that is signed by a Certificate Authority

Answer: D

9. According to the WS-I Basic Profile 1.0a, a conformant WSDL 1.1 portType definition is allowed to use two type operations (that is, Message-Exchange Patterns).

Which two are allowed? (Choose two.)

- A. one-way
- B. notification
- C. solicit-response
- D. request-response

Answer: AD

10. In addition to SAX2 and DOM Level 2, which is supported by JAXP 1.2?

- A. XSLT
- B. JAXB
- C. SAAJ
- D. JDBC

Answer: A

11. Given:

```
<types>
<schema targetNamespace="http://sun.cert/types"
xmlns:tns="http://sun.cert/types"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<xsd:complexType name="Person">
<xsd:all>
<!-- insert code here -->
</xsd:all>
</xsd:complexType>
</schema>
</types>
```

Which two element definitions, when inserted into the given schema fragment, result in a correct schema type definition? (Choose two.)

- A. <xsd:element name="first" type="xsd:string"/>
- B. <xsd:element name="items" type="xsd:long" maxOccurs="5"/>
- C. <xsd:element name="last" type="xsd:string" minOccurs="1" maxOccurs="1"/>
- D. <xsd:element name="first" type="xsd:string" minOccurs="0" maxOccurs="5"/>

Answer: AC

12. According to the JAX-RPC 1.1 XML-to-Java mappings, which three elements or attribute declarations are mapped to a Java primitive wrapper class (for example, java.lang.Short)? (Choose three.)

- A. <xsd:element name="age" type="xsd:short" minOccurs="0"/>
- B. <xsd:element name="age" type="xsd:short" nillable="true"/>
- C. <xsd:element name="age" type="xsd:short" nillable="false"/>
- D. <xsd:attribute name="required" type="xsd:boolean" use="optional"/>
- E. <xsd:attribute name="required" type="xsd:boolean" use="required"/>

Answer: ABD

13. A developer is writing a request-response Web service. An error occurs when the service executes.

Which is true about the Body element of the SOAP reply message?

- A. It must NOT contain any fault elements.
- B. It must contain zero or one fault element.
- C. It must contain an array of fault elements.
- D. It can contain as many fault elements as it needs.

Answer: B

14. Where is the Kerberos ticket embedded in a SOAP header processed?

- A. Web service interaction layer
- B. Web service processing layer
- C. Web service interaction and processing layers
- D. It is an HTML issue and it is NOT related to Web services.

Answer: A

15. Given:

```
<schema targetNamespace="http://sun.cert/types"
xmlns:sun="http://sun.cert/types"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
elementFormDefault="qualified">
<xsd:element name="Person" type="sun:PersonType"/>
<xsd:complexType name="PersonType">
<xsd:sequence>
<xsd:element name="first" type="xsd:string"/>
<xsd:element name="last" type="xsd:string"/>
</xsd:sequence>
</xsd:complexType>
</schema>
```

Assume all XML fragments are well-formed.

Which two instances of Person are correct? (Choose two.)

- A. <Person>
 <first>Monty</first>
 <last>Duke</last>
 </Person>
- B. <t:Person xmlns:t="http://sun.cert/types">
 <first>Monty</first>
 <last>Duke</last>
 </t:Person>
- C. <t:Person xmlns:t="http://sun.cert/types">
 <t:first>Monty</t:first>
 <t:last>Duke</t:last>
 </t:Person>
- D. <p:Person xmlns:p="http://sun.cert/types">
 <f:first xmlns:f="http://sun.cert/types">Monty</f:first>
 <f:last>Duke</f:last>
 </p:Person>

Answer: CD

16. Which SAAJ 1.2 type is used to represent SOAP message header blocks?

- A. org.omg.dom.Document
- B. javax.xml.soap.SOAPPart
- C. javax.xml.soap.DetailEntry
- D. javax.xml.soap.SOAPHeaderElement

Answer: D

17. Given:

```
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns1="http://sun.cert/">
<s:Header>
<ns1:transaction>
<user>root</user>
<transid>9b3e64e326537b4e8c0ff19e953f9673</transid>
</ns1:transaction>
</s:Header>
<s:Body>
<m:StockQuote xmlns:m="http://sun.cert/bar/">
<Quote>
<ns1:symbol>SUNW</ns1:symbol>
<ns1:companyname name="Sun"/>
</Quote>
</s:Body>
</s:Envelope>
```

Which describes this SOAP message?

- A. It is NOT well-formed.
- B. It contains a mandatory header block.
- C. It is WS-I Basic Profile 1.0a compliant.
- D. It does NOT contain the correct namespace declarations.

Answer: A

18. Which two are commonly used as SOAP headers? (Choose two.)

- A. security information
- B. transaction information
- C. postal address information
- D. stock quote request information

Answer: AB

19. Given the type declaration in a WSDL description for a Web service:

```
<element name="PurchaseOrder">
<complexType>
<sequence>
<any maxOccurs="1"/>
</sequence>
</complexType>
</element>
```

The Java code generated by a JAX-RPC service endpoint interface consists of a PurchaseOrder JavaBean.

Which property should the PurchaseOrder JavaBean contain?

- A. `_any` of type `java.lang.String`
- B. `PurchaseOrder` of type `java.lang.Object`
- C. `complexType` of type `java.lang.Object[]`
- D. `_any` of type `javax.xml.soap.SOAPElement`

Answer: D

20. Given:

```
<service name="InventoryServices">
<port name="PurchaseOrder" binding="tns:POBinding">
<soap:address location="http://192.168.0.2:8080/inventory"/>
```

```
</port>
<port name="Invoice" binding="tns:InvoiceBinding">
<soap:address location="http://192.168.0.2:8080/inventory"/>
</port>
</service>
```

Which describes this WSDL extract?

- A. The extract is WS-I Basic Profile 1.0a compliant because both port element names are different.
- B. The extract is NOT WS-I Basic Profile 1.0a compliant because both port elements point to the same location.
- C. The extract is WS-I Basic Profile 1.0a compliant because both port elements point to different binding elements.
- D. The extract is NOT WS-I Basic Profile 1.0a compliant because it contains two port elements in the same service.

Answer: B

### [310-220 Braindumps](#)

#### **Related 310-220 Exams**

[310-220](#) Sun Certified Developer for Java Web Services

---

#### **Other SUN Exams**

<a href="#">310-220</a>	<a href="#">310-630</a>	<a href="#">310-600</a>	<a href="#">310-105</a>	<a href="#">310-027</a>	<a href="#">310-025</a>	<a href="#">310-</a>	<a href="#">310-202</a>
						<a href="#">600Big5</a>	<a href="#">310-043</a>
<a href="#">310-230</a>	<a href="#">310-231</a>	<a href="#">310-615</a>	<a href="#">310-044</a>	<a href="#">310-810</a>	<a href="#">311-203</a>	<a href="#">310-502</a>	<a href="#">310-065</a>
<a href="#">310-011</a>	<a href="#">310-014</a>	<a href="#">310-016</a>					