

350-025 braindumps

Cisco CCIE

350-025: CCIE Service Provider Dial

Practice Exam: 350-025 Exams

Exam Number/Code: 350-025

Exam Name: CCIE Service Provider Dial

Questions and Answers: 400 Q&As

([CCIE](#))



Exam : [350-025](#)

"CCIE Service Provider Dial", also known as 350-025 exam, is a Cisco certification. With the complete collection of exam questions, Just4Study has assembled to take you through 400 Q&As to your 350-025 exam preparation. In the 350-025 exam resources, you will cover every field and category in Cisco Certification helping to ready you for your successful Cisco Certification.

The exam questions cover the latest real test and with all the correct answer. we promise the Q&A for Cisco CCIE 350-025 (CCIE Service Provider Dial) examination of original title complete coverage. 350-025 exam questions help you pass the exam.

Just4Study 350-025 Feature:

* High quality - High quality and valued for the 350-025 Exam: 100% Guarantee to Pass Your 350-025 exam and get your CCIE certification.

* Authoritative - Authoritative braindumps with complete details about 350-025 exam.

* Cheaper - Our Just4Study products are cheaper than any other website. With our completed CCIE resources, you will minimize your **Cisco CCIE** cost and be ready to pass your 350-025 exam on Your First Try, 100% Money Back Guarantee included!

* Free - Try free CCIE demo before you decide to buy it in <http://www.Just4Study.com>.

Just4Study Guarantee:

Just4Study provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if you do not pass the 350-025 exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

Free 350-025 Demo Download

Just4Study offers free demo for CCIE 350-025 exam (CCIE Service Provider Dial). You can check out the interface, question quality and usability of our practice exams before you decide to buy it. We are the only one site can offer demo for almost all products.

The Questions & Answers cover the latest real test and with all the correct answer. we promise the Q&A for **Cisco CCIE 350-025** examination of original title complete coverage. 350-025 Questions & Answers help you pass the exam. Otherwise, we will give you a full refund.

VUE/Prometric Code: 350-025

Exam Name: CCIE Service Provider Dial(CCIE)

Questions and Answers: 400 Q&A

[Cisco 350-025](#) Test belongs to one of the CCIE certified test, if needs to obtain the CCIE certificate, you also need to

participate in other related test, the details you may visit the [CCIE](#) certified topic, in there, you will see all related CCIE certified subject of examination.

Just4Study professional provide CCIE 350-025 the newest Q&A, completely covers 350-025 test original topic. With our complete CCIE resources, you will minimize your CCIE cost and be ready to pass your 350-025 tests on Your First Try, 100% Money Back Guarantee included!

Just4Study Help You Pass Any IT Exam

Just4Study.com offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.

Exam : Cisco 350-025

Title : CCIE Service Provider Dial

1. What type of fiber-optic system is used to distribute cable television signals?

- A. Point to multipoint
- B. Local Area network
- C. Switched
- D. Point to point

Answer: A

2. On a Cisco router with an external modem, what EIA 232 signal will be received by the access server to indicate the presence of an incoming call?

- A. Request To Send
- B. Clear To Send
- C. Data Terminal Ready
- D. Data Set Ready
- E. Loopback

Answer: D

3. The Hold-Down Timer used in Distance Vector protocols:

- A. Sets the time limit of how long a router may keep a packet in its buffer, if the routing protocol is in the process of converging
- B. Determines the number of seconds a router will wait before sending another update to neighbor routers
- C. Sets a specific period for routers to neither accept or advertise a route from a destination where an original route was recently lost
- D. Sets a duration where routes are not accepted from the neighbor router that caused a routing loop

Answer: C

4. For an OC-48 signal (2.5Gb/s), what is the BER (bit error rate) if there is 1 bit error every four days?

- A. 10E-12
- B. 10E-13
- C. 10E-14
- D. 10E-15
- E. 10E-16

Answer: D

5. The network administrator has forgotten the enable password of the router. Luckily, no one is currently logged into the router, but all passwords on the router are encrypted. What should the administrator do to recover the enable password?

- A. Call the Cisco Technical Assistance Center (TAC) for a special code that will erase the existing password.

- B. Reboot the router, press the break key during bootup, boot the router into ROM monitor mode, and modify the configuration register so that the current configuration is ignored during normal bootup
- C. Reboot the router, press the BREAK key during bootup, and boot the router into ROM Monitor mode to erase the configuration, and re-install the entire configuration as it was saved on a TFTP server.
- D. Erase the configuration, boot the router into ROM Monitor mode, press the BREAK key, and overwrite the previous enable password with a new one.

Answer: B

6. Select the group of technologies which are listed in descending order of bandwidth scale:

- A. SDH, X.25, ATM
- B. DWDM, SDH, Frame Relay
- C. DWDM, SDH, ATM
- D. ATM, DWDM, Frame Relay

Answer: C

7. interface Dialer1

ip address 1.1.1.1 255.255.255.0

encapsulation ppp

dialer remote-name Smalluserdialer

string 4540

dialer pool 3

dialer-group 1

What statement about this configuration is true?

- A. This interface is configured for legacy DDR and therefore cannot be used for dialer profiles.
- B. This interface is a logical interface whose configuration is only used for inbound calls on physical interfaces in pool 3.
- C. This logical interface belongs to a group of physical interfaces in group 1.
- D. This configuration is not valid because it is missing the "dialer in-band" command.
- E. This interface will use the name Smalluser instead of the router's hostname for authentication purposes when connecting to the remote peer.
- F. None of the above

Answer: F

8. The purpose of Administrative Distance, as used by Cisco routers, is:

- A. To choose between routes from different routing protocols when receiving updates for the same network
- B. To identify which routing protocol forwarded the update
- C. To define the distance to the destination used in deciding the best path
- D. To be used only for administrative purposes

Answer: A

9. While entering commands on a console, the break key is pressed accidentally and the router reboots. What action could disable this problem?

- A. In configuration mode, enter disable break.
- B. In configuration mode, enter no service break.
- C. Change the configuration register.
- D. Replace the router - this is an invalid response to pressing the break key when past 60 seconds after boot.

Answer: C

10. The purpose of the dialer fast-idle command is:

- A. To decrease the amount of time that an interface is kept down before the next call can be placed - By default, DTR is held low for five seconds.
- B. To specify the amount of time that an interface can remain idle before being disconnected when new outbound calls need to be made

- C. To decrease the interdigit delay between DTMF tones when placing a call
- D. To increase the rate at which disconnected interfaces become available for new outbound calls
- E. To specify the regular idle timeout for high speed non-async interfaces

Answer: B

11. What type of signaling is most relevant to ATM networks supporting SVCs?

- A. H.323
- B. Q.2931
- C. ETSI.761
- D. G.723

Answer: B

12. To have the router verify a called-party number in the incoming setup message for an ISDN BRI call:

- A. Use isdn tei first-call
- B. Include ldn on spid number line
- C. Use isdn answer1
- D. Use isdn caller

Answer: C

13. What Delimits the beginning and the end of the Frame Relay frame?

- A. Address
- B. FCS
- C. Data
- D. Flags
- E. Packets

Answer: D

14. Look at the router configuration above. If this router has a configuration-register setting of 0x102, select the proper boot sequence:

- A. The router will try to use the image "rsp-isv-mz.112-8.P" on slot 0, then attempt to boot from a network server, and finally boot from ROM.
- B. The router will try use the image "rsp-isv-mz.112-8.P" on slot 0, then attempt to boot from any other valid image in flash, and finally boot from ROM.
- C. The router will try to use the image "rsp-isv-mz.112-8.P" on slot 0, and then it will boot from ROM.
- D. The router will try to use the image "rsp-isv-mz.112-8.P" on slot 0, and then attempt to boot from a network server.

Answer: A

15. What effect will this configuration command have?line vty 0 4no password vtypassword

- A. All telnet connections to the router will be denied.
- B. Only one telnet connection at the router will be allowed at a time.
- C. Virtual terminal sessions will not be able to enter enable mode.
- D. Virtual terminal sessions will not be asked a user-level password.
- E. It will have no effect.

Answer: A

16. How long is an ATM cell header?

- A. 5 octets (bytes)
- B. 3 octets (bytes)
- C. 8 octets (bytes)
- D. The size varies by AAL type used

Answer: A

17. The configuration register does NOT retain settings for:

- A. An enabled 'Break' key
- B. The console baud rate
- C. The boot method
- D. An enabled AUX port

Answer: D

18. The NNI specification defines communications between:

- A. An ATM end system and an ATM switch
- B. Two ATM end systems
- C. An ATM device and a non-ATM device
- D. Two ATM switches from different carriers
- E. Two ATM switches

Answer: E

19. What command is used to set the length of time a non-ISDN interface stays down after a call has been completed or has failed and before it is available to dial again?

- A. dialer enable-timeout
- B. dialer holddown
- C. dialer fast-idle
- D. dialer idle-timeout
- E. dialer wait-for-carrier-time

Answer: A

20. What is true about the DLCI field in the Frame Relay header?

- A. It consists of two portions, source and destination, which map data to a logical channel.
- B. It generally has significance only between the local switch and the DTE device.
- C. It is an optional field in the ITU-T specification.
- D. It is present only in data frames sent through the network.

Answer: B

[350-025 Braindumps](#)

Related 350-025 Exams

[350-001](#) *CCIE Cisco Certified Internetworking Expert*

[350-018](#) *CCIE Pre-Qualification Test for Security*

[350-001-LAB](#) *CCIE-ROUTING AND SWITCHING QUALIFICATION (Lab exam)*

[350-030](#) *CCIE Voice Written*

[350-029](#) *CCIE SP Written Exam*

[351-001](#) *CCIE Routing and Switching Written 3.0 Beta*

[350-018-LAB](#) *CCIE Pre-Qualification Test for Security (Lab exam)*

[350-040](#) *CCIE Storage Networking*

[350-022](#) *CCIE Written, Service Provider: DSL*

[350-020](#) *CCIE SP Optical Qualification Exam*

[350-024](#) *CCIE SP IP Telephony Qualification Exam*

[350-027](#) *CCIE Written: Metro Ethernet*

[350-025](#) *CCIE Service Provider Dial*

[351-018](#) *Security 3.0 Beta*

[350-050](#) *CCIE Wireless Beta Written Exam*

[350-021](#) *CCIE SP Cable Qualification Exam*

350-023 CCIE Written: WAN Switching

350-026 CCIE SP Content Networking ENU

350-001GB2312-LAB CCIE-Routing and Switching Written exam

Other Cisco Exams

<u>650-180</u>	<u>642-503</u>	<u>642-382</u>	<u>642-352</u>	<u>642-523</u>	<u>642-979</u>	<u>642-973</u>	<u>350-022</u>
<u>642-651</u>	<u>642-144</u>	<u>646-393</u>	<u>646-003</u>	<u>642-972</u>	<u>642-521</u>	<u>642-891</u>	<u>646-562</u>
<u>642-577</u>	<u>646-976</u>	<u>642-415</u>	<u>642-961</u>				