

## 642-453 braindumps

### Cisco CCVP

#### 642-453: Gateway Gatekeeper Exam

**Practice Exam:** 642-453 Exams

**Exam Number/Code:** 642-453

**Exam Name:** Gateway Gatekeeper Exam

**Questions and Answers:** 60 Q&As

( [CCVP](#) )



Exam : [642-453](#)

"Gateway Gatekeeper Exam", also known as 642-453 exam, is a Cisco certification. With the complete collection of exam questions, Just4Study has assembled to take you through 60 Q&As to your 642-453 exam preparation. In the 642-453 exam resources, you will cover every field and category in Cisco Certification helping to ready you for your successful Cisco Certification.

The exam questions cover the latest real test and with all the correct answer. we promise the Q&A for Cisco CCVP 642-453 (Gateway Gatekeeper Exam) examination of original title complete coverage. 642-453 exam questions help you pass the exam.

#### **Just4Study 642-453 Feature:**

\* High quality - High quality and valued for the 642-453 Exam: 100% Guarantee to Pass Your 642-453 exam and get your CCVP certification.

\* Authoritative - Authoritative braindumps with complete details about 642-453 exam.

\* Cheaper - Our Just4Study products are cheaper than any other website. With our completed CCVP resources, you will minimize your **Cisco CCVP** cost and be ready to pass your 642-453 exam on Your First Try, 100% Money Back Guarantee included!

\* Free - Try free CCVP demo before you decide to buy it in <http://www.Just4Study.com>.

#### **Just4Study Guarantee:**

Just4Study provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if you do not pass the 642-453 exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

#### **Free 642-453 Demo Download**

Just4Study offers free demo for CCVP 642-453 exam (Gateway Gatekeeper Exam). You can check out the interface, question quality and usability of our practice exams before you decide to buy it. We are the only one site can offer demo for almost all products.

The Questions & Answers cover the latest real test and with all the correct answer. we promise the Q&A for **Cisco CCVP 642-453** examination of original title complete coverage. 642-453 Questions & Answers help you pass the exam. Otherwise, we will give you a full refund.

**VUE/Prometric Code: 642-453**

Exam Name: Gateway Gatekeeper Exam( CCVP )

Questions and Answers: 60 Q&A

[Cisco 642-453](#) Test belongs to one of the CCVP certified test, if needs to obtain the CCVP certificate, you also need

to participate in other related test, the details you may visit the [CCVP](#) certified topic, in there, you will see all related CCVP certified subject of examination.

Just4Study professional provide CCVP 642-453 the newest Q&A, completely covers 642-453 test original topic. With our complete CCVP resources, you will minimize your CCVP cost and be ready to pass your 642-453 tests on Your First Try, 100% Money Back Guarantee included!

### **Just4Study Help You Pass Any IT Exam**

*Just4Study.com offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.*

Exam : CISCO 642-453

Title : Gateway Gatekeeper(GWGK)

1. When a WAN link problem occurs, it takes over three minutes for IP phones to become registered with the SRST gateway. What is the most likely cause of this?

- A. The WAN link is bouncing.
- B. The keepalive timer in the SRST gateway is set too long.
- C. Each phone has a list of two alternate Cisco Unified CallManager systems, and it tries to register with each before registering with the SRST gateway.
- D. The SRST gateway is an MGCP gateway, and it must stop the MGCP process and switch over to the default H.323 process to initiate the SRST process.

Answer: C

2. Refer to the exhibit. Which dial peer will send calls to the PSTN via the T1 configured as shown?

A. dial-peer voice 1 pots

destination-pattern 9T

port 3/0:0

B. dial-peer voice 1 pots

destination-pattern 9T

port 3/0:1

C. dial-peer voice 1 pots

destination-pattern 9T

port 3/0:24

D. dial-peer voice 1 pots

destination-pattern 9T

session target 3/0:0

E. dial-peer voice 1 pots

destination-pattern 9T

session target 3/0:1

F. dial-peer voice 1 pots

destination-pattern 9T

session target 3/0:24

Answer: A

3. Which describes a proper CAC implementation in an H.323 network that uses directory gatekeepers?

A. The bandwidth commands for each zone that is registered with the directory gatekeeper are included in the directory gatekeeper configuration.

B. The zone gatekeepers maintain the bandwidth commands and the directory gatekeeper is only responsible for dial plan resolution.

C. The zone gatekeeper negotiates bandwidth requirements with the target zone gatekeeper by means of an LRQ

message forwarded by the directory gatekeeper.

D. The directory gatekeeper controls call bandwidth usage between the zones.

Answer: B

4. You are working with a client who is interested in deploying a distributed IP telephony call-processing solution among the three corporate campuses. Each campus will have a Cisco Unified CallManager cluster and a gateway to the PSTN. Which three steps are required for a successful gatekeeper deployment? (Choose three.)

A. determining if each zone will be supported by more than one gatekeeper

B. determining the intrasite modem and fax traffic patterns

C. ensuring the correct location of voice gateways in the network

D. provisioning a common codec for all WAN connections

E. implementing the correct WAN topology

F. determining if gatekeeper redundancy or high availability is required

Answer: DEF

5. Refer to the exhibit. Which message ID can be used to track this call from the requesting endpoint?

A. 8204

B. 10.100.100.99

C. 10.200.99.99

D. 49579

E. 10.100.100.100

F. 1640003356

Answer: A

6. You are adding a gatekeeper to an H.323 network to provide Call Admission Control. You need to be able to support three concurrent G.711 calls from a specified zone to any other zone. How much interzone bandwidth should be configured in the gatekeeper?

A. 192 Kbps

B. 240 Kbps

C. 384 Kbps

D. 480 Kbps

Answer: C

7. Which gatekeeper configuration will send all calls between zone hardware and zone appliances through the IP-to-IP gateway in the VIA zone?

A. gatekeeper

zone local hardware acme.com 192.168.1.1

zone local appliances acme.com

zone local via acme.com

zone prefix hardware 408.....

zone prefix appliances 415.....

no shut

B. gatekeeper

zone local hardware acme.com 192.168.1.1

zone local appliances acme.com

zone local via acme.com invia via outvia via

zone prefix hardware 408\*

zone prefix appliances 415\*

no shut

C. gatekeeper

zone local hardware acme.com 192.168.1.1

invia VIA outvia VIA

zone local appliances acme.com invia VIA outvia VIA

zone prefix hardware 408.....

zone prefix appliances 415.....

no shut

D. gatekeeper

zone local hardware acme.com 192.168.1.1 in via out via

zone local appliances acme.com in via out via

zone local via acme.com

zone prefix hardware 408\*

zone prefix appliances 415\*

no shut

Answer: D

8. In which three situations would an IP-to-IP gateway be useful? (Choose three.)

A. two organizations have merged and both use SCCP signaling

B. an organization would like to migrate from H.323 to SIP

C. an organization has deployed a SIP IP telephony solution and needs to connect to a SIP service provider

D. an organization needs to migrate from a Cisco Unified CallManager IP telephony solution based on SCCP to an H.323 solution.

E. an organization using H.323 needs to integrate an acquisition that also uses H.323

F. an organization needs to integrate larger PSTN gateways into their SIP network

Answer: BCE

9. Refer to the exhibit. Horst's Helicopters has a centralized Cisco Unified CallManager deployment, with SRST implemented on MGCP gateways at the remote sites. The WAN link to Seattle has failed. All phones in Seattle have registered to the SRST gateway and can call each other internally, but all outside calls fail. Based on the output shown in the exhibit, what is the most likely solution to the problem?

A. configure MGCP fallback on the gateway

B. add the isdn outgoing-voice command to the configuration

C. call the phone provider and report that the PRI link is down

D. enable the outgoing POTS dial peer with the no shutdown command

Answer: A

10. Highland Park Property Development is integrating a Cisco Unified CallManager system with the existing PBX via an E1 QSIG trunk. During testing, the first 15 calls work normally. After 15 simultaneous calls, new calls have no audio path when they are established. How can this problem be resolved?

A. Add the command isdn contiguous-bchan to the serial interface.

B. Change the channel selection order from descending to ascending.

C. Add the command isdn negotiate-bchan to the serial interface.

D. Increase the ISDN T302 timer to allow more time for call setup.

Answer: A

11. You have a client who is designing a gateway solution for an IP communications network. The T1 needs to support ANI for both incoming and outgoing calls. How should the gateway be configured?

A. Configure an MGCP gateway so that there are two DS-0 groups on the T1 from the PSTN, one to send ANI and one to receive ANI.

B. Configure an H.323 gateway so that there are two DS-0 groups on the T1 from the PSTN, one to send ANI and one to receive ANI.

C. Configure an MGCP gateway so that there is a single DS-0 group on the T1 to the PSTN, to both send and receive ANI.

D. Configure an H.323 gateway so that there is a single DS-0 group on the T1 to the PSTN, to both send and receive ANI.

Answer: B

12. Which debug command can be used to troubleshoot an issue with a Tcl script?

- A. debug tcl script
- B. debug call script
- C. debug custom script
- D. debug voice application

Answer: D

13. When an IP-to-IP gateway registers with a gatekeeper, what type of endpoint is the gateway listed as?

- A. VOIP
- B. IP-IP
- C. gateway
- D. H323-GW

Answer: D

14. When a C5510 DSP is configured for conferencing, what other services can it be configured to support?

- A. transcoding
- B. supplementary services
- C. voice port termination
- D. no other services

Answer: D

15. Users are complaining that they are not seeing caller names on calls received from the PSTN. Which debug command can be used to troubleshoot this problem?

- A. debug isdn setup
- B. debug isdn q921
- C. debug isdn q931
- D. debug ccs signal
- E. debug vpm signal

Answer: C

16. Refer to the exhibit. Your customer is using BRIs to the PSTN. Inbound calls can be made without error. However, outbound calls only succeed if there has been a recent inbound call. What can be done to correct this issue?

- A. Disable status checking for POTS dial peers so outbound call setup will activate the BRI.
- B. Configure SPIDs on the BRI so that outbound calls are sent to the correct number.
- C. Change the dial peer hunt logic so the appropriate dial peer is always used.
- D. Configure preferences to always select dial peer 3.

Answer: A

17. Refer to the exhibit. On a router running Cisco IOS version 12.3(14)T, an auto-attendant Tcl script is loaded and a warning message is displayed, stating that the operator parameter has not been registered. See the exhibit for an example of the error. What must you do to continue?

- A. nothing, the warning may be ignored
- B. register the application with the gatekeeper
- C. register the application parameters with the gatekeeper
- D. register the application parameters with the application
- E. register the application with the Cisco Unified CallManager
- F. register the application parameters with the Cisco Unified CallManager

Answer: A

18. Which statement is true regarding Cisco modem relay?

- A. It supports the V.150.1 signaling standard.
- B. It is supported by some third party vendors.
- C. It requires that codec complexity be set to "high" or "flex mode".

- D. It uses more bandwidth than modem pass-through.
- E. It is supported on H.323, MGCP, SIP, and SCCP gateways.

Answer: C

19. Which two dial plan components are required to implement TEHO? (Choose two.)

- A. internal numbering plan
- B. path selection
- C. Class of Service
- D. digit manipulation
- E. call coverage

Answer: BD

### [642-453 Braindumps](#)

#### **Related 642-453 Exams**

[642-446](#) *Implementing Cisco Unified Communications IP Telephony Part 1*

[642-425](#) *IP Telephony Troubleshooting*

[642-445](#) *Cisco IP Telephony for Release 5.x*

[642-453](#) *Gateway Gatekeeper Exam*

[642-452](#) *Gateway Gatekeeper Exam (GWGK)*

#### **Other Cisco Exams**

[350-022](#)    [646-203](#)    [646-151](#)    [642-741](#)    [642-144](#)    [642-736](#)    [642-067](#)    [642-521](#)

[350-030](#)    [642-066](#)    [642-425](#)    [646-573](#)    [650-180](#)    [642-481](#)    [646-046](#)    [642-801](#)

[642-321](#)    [642-731](#)    [350-020](#)    [350-027](#)