

920-136 braindumps

Nortel NCDS

920-136: NCDS - Ethernet Switching Solutions

Practice Exam: 920-136 Exams

Exam Number/Code: 920-136

Exam Name: NCDS - Ethernet Switching Solutions

Questions and Answers: 66 Q&As

([NCDS](#))



Exam : [920-136](#)

"NCDS - Ethernet Switching Solutions", also known as 920-136 exam, is a Nortel certification. With the complete collection of exam questions, Just4Study has assembled to take you through 66 Q&As to your 920-136 exam preparation. In the 920-136 exam resources, you will cover every field and category in Nortel Certification helping to ready you for your successful Nortel Certification.

The exam questions cover the latest real test and with all the correct answer. we promise the Q&A for Nortel NCDS 920-136 (NCDS - Ethernet Switching Solutions) examination of original title complete coverage. 920-136 exam questions help you pass the exam.

Just4Study 920-136 Feature:

* High quality - High quality and valued for the 920-136 Exam: 100% Guarantee to Pass Your 920-136 exam and get your NCDS certification.

* Authoritative - Authoritative braindumps with complete details about 920-136 exam.

* Cheaper - Our Just4Study products are cheaper than any other website. With our completed NCDS resources, you will minimize your **Nortel NCDS** cost and be ready to pass your 920-136 exam on Your First Try, 100% Money Back Guarantee included!

* Free - Try free NCDS demo before you decide to buy it in <http://www.Just4Study.com>.

Just4Study Guarantee:

Just4Study provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if you do not pass the 920-136 exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

Free 920-136 Demo Download

Just4Study offers free demo for NCDS 920-136 exam (NCDS - Ethernet Switching Solutions). You can check out the interface, question quality and usability of our practice exams before you decide to buy it. We are the only one site can offer demo for almost all products.

The Questions & Answers cover the latest real test and with all the correct answer. we promise the Q&A for **Nortel NCDS 920-136** examination of original title complete coverage. 920-136 Questions & Answers help you pass the exam. Otherwise, we will give you a full refund.

VUE/Prometric Code: 920-136

Exam Name: NCDS - Ethernet Switching Solutions(NCDS)

Questions and Answers: 66 Q&A

[Nortel 920-136](#) Test belongs to one of the NCDS certified test, if needs to obtain the NCDS certificate, you also need to participate in other related test, the details you may visit the [NCDS](#) certified topic, in there, you will see all related NCDS certified subject of examination.

Just4Study professional provide NCDS 920-136 the newest Q&A, completely covers 920-136 test original topic. With our complete NCDS resources, you will minimize your NCDS cost and be ready to pass your 920-136 tests on Your First Try, 100% Money Back Guarantee included!

Just4Study Help You Pass Any IT Exam

[Just4Study.com](#) offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.

Exam : Nortel 920-136

Title : NCDS - Ethernet Switching Solutions

1. Internet Group Management Protocol (IGMP) is used by IP Multicast routers to learn about the existence of host group members on their directly attached subnets. Which statement about IGMP is true?

A. The IP Multicast routers get this information by listening for IP hosts broadcasting IGMP queries and reporting their host group memberships.

B. The IP Multicast routers get this information by broadcasting IGMP queries and listening for IP hosts reporting their host group memberships.

C. The IP Multicast routers get this information by recognizing the modified MAC address of a Multicast packet and adding that MAC address to the Multicast tree.

D. The IP Multicast routers get this information by listening for Multicast Servers broadcasting IGMP queries and listening for IP hosts reporting their host group memberships.

Answer: B

2. A customer is adding fiber support onto an existing 48 port 5510. Their current installation is using all UTP ports on the switch. They need to install two 1000 Base-SX SFPs into the SFP slots. Which statement is true about the requirements for this installation?

A. The Console port requires SFPs.

B. Only one 1000 Base-SX GBIC will be supported.

C. It will require ports 47 and 48 to be unplugged before using SFPs.

D. It will require the power to the unit is turned off before installing GBICs.

Answer: C

3. A customer is selecting an Ethernet Routing Switch to be used to route legacy protocols. It must be able to route IPX traffic and dynamically advertise IPX routes in a network. Which Ethernet Routing Switch will meet these requirements?

A. 1600

B. 5500

C. 8300

D. 8600

Answer: D

4. A customer has a stack of Ethernet Switch 470-48Ts. The uplinks to the network core are via two Gigabit uplink ports from the first Ethernet Switch 470-48T in the stack to a single Ethernet Routing Switch 8600. The links are not part of a MultiLink Trunk (MLT), and spanning tree is running. This results in one of the links always being blocked and recovery time unacceptably long when the active uplink fails. They need to have both links active to increase the bandwidth to the core, and at the same time provide better redundancy.

What is the preferred Nortel solution for the customer?

- A. Move one of the uplinks to another Ethernet Switch 470-48T in the stack and disable spanning-tree on both uplinks.
- B. Move one of the uplinks to another Ethernet Switch 470-48T in the stack and enable Equal Cost Multi-Path (ECMP) on the uplinks.
- C. Move one of the uplinks to another Ethernet Switch 470-48T in the stack, and group the two uplinks in a Distributed MultiLink Trunk (DMLT).
- D. Move one of the uplinks to another Ethernet Switch 470-48T in the stack, and ensure that the two uplinks terminate on different modules in the Ethernet Routing Switch 8600.

Answer: C

5. A customer is connecting a new remote office to the corporate network. The office will be connected to the network core through a fiber link that terminates at an Ethernet Routing Switch 8600 almost 40km away. It will provide 10/100 Ethernet access for ten people, two printers and one file server at the remote location. The switch that will be installed must meet the requirements below.

The switch must support IEEE 802.3af Power over Ethernet.

Differentiated Services (DiffServ) and advanced IP Policies must be supported to provide IP QoS.

The switch must support the 1000Base-XD Gigabit Interface Connector (GBIC) or Small Form-Factor Pluggable (SFP GBIC) for the uplink connection.

Which switch meets these requirements?

- A. Ethernet Switch 425-24T
- B. Ethernet Switch 470-48T
- C. Ethernet Routing Switch 1648T
- D. Ethernet Switch 460-24T-PWR

Answer: D

6. An engineer implemented a core network consisting of four Ethernet Routing Switch 8600s and needs the ability to build a redundant core. Which feature would be used to provide redundancy and fail-over times?

- A. Spanning Forest
- B. Multi-Link Trunking
- C. Protocol Based VLANs
- D. Split Multi-Link Trunking

Answer: D

7. A customer is implementing video conferencing devices that require Power over Ethernet (PoE). They are planning to use an Ethernet Routing Switch 8310 chassis for this deployment. They would also like to install 8600 modules in the chassis. Which statement about this customer scenario is true?

- A. Both PoE and 8600 modules are supported in the 8310 chassis.
- B. Neither PoE or 8600 modules are supported in the 8310 chassis.
- C. 8310 chassis does not support PoE, but will support 8600 modules.
- D. PoE could be supplied via the 8310 chassis, but will not support 8600 modules.

Answer: D

8. A carrier needs to support OC-12c (STM-4) and OC-3c (STM-1) on an Ethernet Routing Switch 8600. What is a minimal configuration needed to support this requirement?

- A. one ATM module and no MDAs
- B. one OC-12c/STM-4 module and one OC-3c/STM-1 module
- C. one OC-12c/STM-4 ATM MDA and one OC-3c/STM-1 ATM MDA on an ATM module
- D. one OC-12c/STM-4 ATM MDA on the first ATM module and one OC-3c/STM-1 ATM MDA on the second ATM module

Answer: C

9. A customer is selecting an Ethernet Routing Switch to be installed in a wiring closet. The switch must support 10 Gbps connections and have redundant power. Which two Ethernet Routing Switches will meet these requirements?

(Choose two.)

- A. 1600
- B. 5520
- C. 5530
- D. 8600

Answer: CD

10. A customer is expressing concern about reliability for their single uplink connection to the wiring closet. The switches in the wiring closet support Distributed Multi-Link Trunking (DMLT). What can be done so the Ethernet Routing Switch 8600 can eliminate a single point of failure for the lowest price?

- A. Add a second switch fabric module.
- B. Duplicate the trunk elements in software.
- C. Duplicate the trunks across separate modules using DMLT.
- D. Configure multiple Ethernet Routing Switch 8600s using Split Multi-Link Trunking (SMLT).

Answer: C

[920-136 Braindumps](#)

Related 920-136 Exams

[920-141](#) *NNCDS-Communication Server(cs)1000 release 4.0*

[920-256](#) *Nortel VPN Router Ris.7.0 Solutions(NCDS)*

[920-136](#) *NCDS - Ethernet Switching Solutions*

[920-165](#) *NCDS-Contact Center Ris.6.0 Exam*

[920-203](#) *nncds passport 7000/15000*

[920-242](#) *nncds-contivity vpn switch*

[920-125](#) *NNCDS Succession BCM 3.0 Exam*

[920-209](#) *NCDS-Multiservice Switch 7400/15000/20000*

[920-124](#) *NNCDS -Ethernet Switching Exam*

Other Nortel Exams

[920-259](#) [920-253](#) [920-122](#) [920-216](#) [920-333](#) [920-197](#) [920-112](#) [920-551](#)

[922-098](#) [922-054](#) [920-461](#) [920-166](#) [920-209](#) [920-021](#) [920-139](#) [920-191](#)

[922-059](#) [922-081](#) [920-501](#) [920-246](#)