

920-468 braindumps

Nortel NCSE

920-468: Nortel VPN Router RIs.7.0 Advanced Configuration & Mgmt

Practice Exam: 920-468 Exams

Exam Number/Code: 920-468

Exam Name: Nortel VPN Router RIs.7.0 Advanced Configuration & Mgmt

Questions and Answers: 59 Q&As

([NCSE](#))



"Nortel VPN Router RIs.7.0 Advanced Configuration & Mgmt", also known as 920-468 exam, is a Nortel certification. With the complete collection of exam questions, Just4Study has assembled to take you through 59 Q&As to your 920-468 exam preparation. In the 920-468 exam resources, you will cover every field and category in Nortel Certification helping to ready you for your successful Nortel Certification.

Exam : [920-468](#)

The exam questions cover the latest real test and with all the correct answer. we promise the Q&A for Nortel NCSE 920-468 (Nortel VPN Router RIs.7.0 Advanced Configuration & Mgmt) examination of original title complete coverage. 920-468 exam questions help you pass the exam.

Just4Study 920-468 Feature:

* High quality - High quality and valued for the 920-468 Exam: 100% Guarantee to Pass Your 920-468 exam and get your NCSE certification.

* Authoritative - Authoritative braindumps with complete details about 920-468 exam.

* Cheaper - Our Just4Study products are cheaper than any other website. With our completed NCSE resources, you will minimize your **Nortel NCSE** cost and be ready to pass your 920-468 exam on Your First Try, 100% Money Back Guarantee included!

* Free - Try free NCSE demo before you decide to buy it in <http://www.Just4Study.com>.

Just4Study Guarantee:

Just4Study provides the most competitive quality of all exams for the customers, we guarantee your success at the first attempt with only our Certification Question&Answers, if you do not pass the 920-468 exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

Free 920-468 Demo Download

Just4Study offers free demo for NCSE 920-468 exam (Nortel VPN Router RIs.7.0 Advanced Configuration & Mgmt). You can check out the interface, question quality and usability of our practice exams before you decide to buy it. We are the only one site can offer demo for almost all products.

The Questions & Answers cover the latest real test and with all the correct answer.we promise the Q&A for **Nortel NCSE 920-468** examination of original title complete coverage.920-468 Questions & Answers help you pass the exam. Otherwise,we will give you a full refund.

VUE/Prometric Code: 920-468

Exam Name: Nortel VPN Router RIs.7.0 Advanced Configuration & Mgmt(NCSE)

Questions and Answers: 59 Q&A

[Nortel 920-468](#) Test belongs to one of the NCSE certified test, if needs to obtain the NCSE certificate, you also need to participate in other related test, the details you may visit the [NCSE](#) certified topic, in there, you will see all related NCSE certified subject of examination.

Just4Study professional provide NCSE 920-468 the newest Q&A, completely covers 920-468 test original topic. With our complete NCSE resources, you will minimize your NCSE cost and be ready to pass your 920-468 tests on Your First Try, 100% Money Back Guarantee included!

Just4Study Help You Pass Any IT Exam

[Just4Study.com](#) offers incredible career enhancing opportunities. We are a team of IT professionals that focus on providing our customers with the most up to date material for any IT certification exam. This material is so effective that we Guarantee you will pass the exam or your money back.

Exam : Nortel 920-468

Title : Nortel VPN Router Rls.7.0 Advanced Configuration & Mgmt

1. To enable Fail-over support in a VPN Router configuration, a technician is setting up Static Tunnel Fail-over for Branch Office Tunnels. Primary and subsequent static routes will be created. To provide the required Fail-over support, how will the primary tunnel be configured?

- A. It must be nailed up.
- B. It must use RIP only.
- C. It must use OSPF only.
- D. It must be a virtual tunnel.

Answer: A

2. A customer would like their remote users to be able to establish a VPN tunnel with an alternate VPN Router, if the primary VPN Router fails.

What would need to be configured to ensure Fail-over protection?

- A. Demand Services
- B. Firewall and DHCP settings on the remote PC
- C. Only LDAP group parameters
- D. VPN Router user tunnel for IPSec fail-over service

Answer: D

3. Virtual Router Redundancy Protocol (VRRP) has been configured on the VPN Routers of a customer's network. However, all of the traffic is being routed to the Backup and not the Master. What could be a possible reason for this problem?

- A. The Virtual Router ID (VRID) is not configured correctly.
- B. The Backup and Master VPN Routers are running two different versions of code.
- C. The Priority Value of the Master is set to 100, and the Backup is set to a higher value.
- D. The authentication string in the Authentication Data field is not set.

Answer: C

4. Virtual Router Redundancy Protocol (VRRP) has been configured to run as master on a physical interface of a VPN Router. Three additional interfaces, each in a separate interface group, have been associated with this master VRRP interface. Assume one of the three additional interface has gone down. How will the VPN Router react?

- A. It will force a VRRP fail-over.
- B. It will reroute traffic to the associated VRRP master interface.
- C. It will reroute traffic to one of the two remaining additional interface groups.
- D. No action necessary, since two additional interfaces are available to the master.

Answer: A

5. Virtual Router Redundancy Protocol (VRRP) has been configured to run as master on a physical interface of a VPN Router. Two additional interface groups have been associated with this master VRRP interface by use of an interface group. Assume these two additional interface groups have gone down. Which statement describes the state of the VRRP master interface in this scenario?

- A. The VRRP master interface remains in the up state as long as the master physical interface is up.
- B. The VRRP master interface stays in the down state until all associated interface groups come up.
- C. The VRRP master interface goes into a hold state until at least one of the two interface groups comes up.
- D. The VRRP master interface goes into a down state until at least one of the two interface groups comes up.

Answer: B

6. In a VPN Router network, a technician has enabled the Fail-over feature so that all remote users working offsite using the Nortel VPN Client will attempt to connect to one or more alternate VPN Router devices if the primary VPN Router fails. Which statement is true regarding the IP addresses specified for the alternate VPN Router devices in the Fail-over?

- A. The IP addresses must be for public interfaces.
- B. The IP addresses must be for private interfaces.
- C. The IP addresses must match the VPN Router management interface address.
- D. The IP addresses must match the primary VPN Router interface address.

Answer: A

7. A merchant requires the most stringent proof of identity requirements because its certificate is used in the Server Secure Sockets Layer (SSL) protocol to both authenticate the merchant site and is also used as part of the keying material used to encrypt customer credit card information. Which class of certification would you recommend for this merchant?

- A. Class One
- B. Priority Class
- C. Class A1
- D. Class Three

Answer: D

8. Employees at the company headquarters and out in the field have found that they are moving from an Ethernet connection to a wireless connection and back, on a regular basis while still having a VPN tunnel established. A network administrator has been tasked with finding a solution that preserves the IPSec tunnel while roaming within the LAN, without affecting applications that use the VPN tunnel. Which solution would you recommend for this customer?

- A. IPSec fail-over
- B. Nortel IPSec Mobility
- C. Tunnel Persistence Mode
- D. Virtual Router Redundancy Protocol (VRRP)

Answer: B

9. A customer's VPN Router is configured to authenticate users by their user certificates. Each user is placed into a default group upon successful authentication. Since the customer's user base is growing rapidly, they would like to create a user group for each department within the company and have each user be placed into respective groups upon successful authentication.

Which approach will support this solution?

- A. Configure a 'User Access Policy' from the user's group IPsec configuration screen.
- B. Configure a 'User Access Policy' in the Certification Authority certificate details section to determine group membership.
- C. Use a separate Certification Authority (CA) for each group, and set each group as the 'Default Group' for its respective CA certificate.
- D. Configure 'Group Access Control' in the Certification Authority certificate details section to use the Subject DN of the user certificate to determine group membership.

Answer: D

10. A customer has eight VPN Router 5000 systems that share an external LDAP server. Users are authenticated by the switch, which requires a valid user certificate and a user account in the LDAP database. The IT Director is concerned that someone may gain access to confidential employee information during LDAP authentication between the VPN Router and the external LDAP server. What can be done to ensure security?

- A. Transfer the user accounts from the external LDAP database to an external RADIUS server.
- B. Create a separate subnet just for the external LDAP database server to isolate its network traffic.
- C. Configure the VPN Router and the external LDAP server to communicate via Secure Socket Layer (SSL).
- D. Switch the external LDAP database to an internal LDAP database on each switch to avoid authentication over the network.

Answer: C

11. A network administrator has worked with and configured Secure Sockets Layer (SSL) /Transport Layer Security (TLS) on their VPN Router and has been made aware of a security vulnerability involving Cipher Block Chaining. What information is important to the network administrator?

- A. Block ciphers are the most common in cryptography and are therefore prone to security risks.
- B. Block ciphers split the message into fixed blocks of text and encrypt them individually.
- C. Optional padding has been added as a countermeasure and the VPN Router default setting has been set to Not Enabled.
- D. The end of the message is padded with random contents to ensure the entire message is aligned on block boundaries.

Answer: C

12. A high-profile customer dealing with electronic commerce requires non-repudiation of a signature and needs a way to guarantee both the integrity of the data and the authenticity of a sender. You recommend the use of digital certificates and the associated digital signature algorithm. Which statement about the digital signature algorithm is false?

- A. The digital signature is computed using a set of rules and a set of parameters such that the identity of the signatory and integrity of the data can be verified.
- B. Each user possesses a private and public key pair. Anyone can verify the signature of a user by employing that user's public key.
- C. The digital signature shows who actually ordered the merchandise and but cannot guarantee that the information on the order has not been changed.
- D. A private key is restricted for signature use.

Answer: C

13. A customer would like to implement an authentication method that can verify both devices involved with each secure connection. Which scenario would require the use of digital certificates?

- A. The LDAP Server Secure Sockets layer (SSL) encryption that provides privacy between the VPN Router and an external LDAP server.
- B. The setup of an IPSec tunnel when token security is used in place of user ID and password authentication.
- C. A distributed security system that uses an authentication server to verify dial-up connection attributes and authenticate connections.
- D. The setup of the IPSec connection between a VPN Router and a Windows 2000 client.

Answer: A

14. A customer needs to provide fail-over support capability on their statically routed branch office tunnels and would like to configure the VPN Routers with redundant static routes. Which step can be used to configure static tunnels for fail-over?

- A. Create a single static tunnel.
- B. Give subsequent static routes a lower cost.
- C. Configure static tunnel fail-over using keep-alive and/or idle time out.

D. Give the primary static route a higher cost.

Answer: C

15. A VPN Router customer is using certificate authentication for user and branch office tunnels. A supervisor has suggested configuring Certificate Management Protocol (CMP) on the VPN Routers company wide in order to reduce the administrator's workload. In what way would the configuration of CMP benefit the administrator?

A. CMP automates the processes of Certificate Revocation List (CRL) updates and CRL distributions to all VPN Routers.

B. CMP allows the VPN Router to act as a Certification Authority (CA) for other VPN Routers on the network.

C. CMP automates the process of client certificate distribution, so the clients do not need to generate a certificate request.

D. CMP offers management of the entire certificate and key life cycle for the server of the VPN Router.

Answer: D

[920-468 Braindumps](#)

Related 920-468 Exams

[920-448](#) *nncse-alteon security*

[920-453](#) *ncse callpilot 2.x/3.0 unified messaging*

[920-804](#) *Nortel technology standards and protocols for converged networks*

[920-441](#) *nncde contivity security exam*

[920-447](#) *nncse-contact center exam*

[920-468](#) *Nortel VPN Router RIs.7.0 Advanced Configuration & Mgmt*

[920-458](#) *CSE- CallPilot RIs.4.0 Unified Messaging*

[920-452](#) *NCSE-Communication Server 1000 RIs.4.0*

[920-443](#) *nncse-succession 1000/1000m rIs.3.0*

[920-449](#) *nncse contivity security*

Other Nortel Exams

[920-134](#)

[920-180](#)

[922-020](#)

[922-097](#)

[920-158](#)

[920-460](#)

[920-233](#)

[920-251](#)

[920-270](#)

[920-124](#)

[922-089](#)

[920-167](#)

[922-059](#)

[920-209](#)

[920-471](#)

[920-114](#)

[920-165](#)

[922-053](#)

[920-501](#)

[920-321](#)