

Exam : [HP HP0-Y26](#)

Title : **Building a Complete HP
ProCurve Mobility Solution**

Version : **Demo**

1. You have verified that an HP ProCurve Switch 3500yl is correctly configured for PIM dense mode. The switch's IGMP table shows active hosts that are members of multicast group 239.193.22.22. The multicast is in progress, and all hosts are receiving the content. However, the multicast group does not appear in the switch's PIM route table.

What does this indicate about the 239.193.22.22 multicast group?

- A. The switch is forwarding the multicast at Layer 2.
- B. Other multicast routers are configured for PIM sparse.
- C. The server and IGMP hosts are in different VLANs.
- D. The switch is Querier for the group.

Answer: A

2. You have enabled Dynamic ARP Protection on an HP ProCurve 5406zl switch. When is it necessary to define IP-to-MAC address bindings?

- A. when you must lock down the switch's IP addresses to its base MAC address
- B. when you must specify clients connected to untrusted ports
- C. when you must identify devices that do not use DHCP, but have a static IP address assigned
- D. when you must protect uplink ports that connect to other switches that do not support Dynamic ARP Protection
- E. when you must provide security to ports where different clients may connect at different times

Answer: C

3. You must use the web management interface of an HP MSM710 Controller to perform a manual upgrade of the controller's software. In the management interface, which location must be specified as the source for the software file?

- A. TFTP server
- B. your workstation
- C. controller auxiliary port
- D. your FTP server

Answer: B

4. You must configure an HP ProCurve Switch 8212zl to be the Backup router for a VRID associated with VLAN 10. What must be true of the virtual IP address for the VRID on this router?

- A. It must be an address assigned to a multi-netted interface.
- B. It must be an address that is not assigned to any interface on either router.
- C. It must match the Backup router's address for the VLAN 10 interface.
- D. It must match the Owner router's address for the VLAN 10 interface.

Answer: D

5. You must configure an HP ProCurve Switch 8212zl to be the Owner of a VRID associated with VLAN 10. What must be true of the virtual IP address for the VRID?

- A. It must be an address on a multi-netted interface.
- B. It must match the router's address for the VLAN 10 interface.
- C. It must match the address assigned to VLAN 10 on the Backup router.
- D. It must use a classful network mask.

Answer: B